

# PRODUCT DATA SHEET

# MEWAR – 315W

Mewar-315W is a woven geotextile made up of high tenacity polypropylene tapes that are woven to form stable and durable structure, which allows the tapes to maintain their relative position. It is non-biodegradable and resistant to ultraviolet degradation, rotting, and most soil chemicals. MEWAR-315W is manufactured by Mewar Polytex Group in India, and it conforms to the property values listed below.

PROPERTY	TEST METHOD	MARV English
Tensile Strength (Grab)	ASTM D4632	315 x 315 lbs
Elongation	ASTM D4632	15%
CBR Puncture	ASTM D6241	900 lbs
Trapezoidal Tear	ASTM D4533	120 x 120 lbs
UV Resistance (500 hrs)	ASTM D4355	70%
Apparent Opening Size (AOS)*	ASTM D4751	40 US Std. Sieve
Permittivity	ASTM D4491	0.05 sec <sup>-1</sup>
Water Flow Rate	ASTM D4491	3 gpm/ft <sup>2</sup>

\*Maximum Average Roll Value

Disclaimer: Mewar Polytex Group, as a whole, assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. Nothing contained herein should be construed as creating an expressed or implied warranty, including warranties of merchantability and fitness, each of which is hereby disclaimed. There are no warranties that extend beyond the description on the face hereof. This document should not be construed as engineering advice. Always consult the project engineer for project specific requirements. The end user assumes sole responsibility for the use of this information and product. The property values listed above are subject to change without notice.